SIDE LOADING SYSTEM

Maximizing the efficiency of the paper cutter

Side loading system eliminates time loss between the squaring up of stack edges and the cutting operation.

Proposing total rationalization in all directions from energy conservation to work efficiency and cutting accuracy.

Grippers pull-in system

The grippers grip the sheets and pull them in, thus avoiding the sheets being misaligned which was a problem when they were manually transferred by operators.

Gripping performance

The stack of paper set to the maximum height does not cause any sheets to be misaligned, contributing to productivity.

Energy conserved operation

When used with the paper jogger with the feed-in function, the paper does not need to be transferred at all, reducing the load on the operators.

Storing table

The storing air table, which holds the sheets until the cutting operation is finished,



Providing the most flexible system design with an original order system

What is the "Original Order System"?

The dedicated planner will promptly develop the optimum system plan for you, altering the standard specifications to suit your specific needs such as dimensional changes and irregular layout for space conservation or changes in accordance with your special machine movements.

Feel free to talk to our sales representative for more details.



Lay-out plan

RC-137DX / RSL1.2L / Paper jogger with feed-in function



Machine dimensions



Machine specifications

CONTROLLER

Maximum paper size	35 1/3"×51"	900×1300mm
Maximum height of supplied	6 1/2"	165mm
Minimum height of supplied	1 1/8"	30mm
Table height	33 1/2"~37 1/3"	850~950mm
Paper feed cycle	30sec	
Applicable paper cutters	Size 137 to 170	
Table size	59"×39 1/3"	1500×1000
Weight	1056 lbs	480kg
Total electrical capacity	1.0kw	



ITOTEC CO.,LTD Funada No.10, Inuyama, Aichi-pref, 484-0912, JAPAN. Phone: 81-568-67-5311 Fax : 81-568-68-0495 The specifications listed here may be revised without any prior notice for the purpose of improvements.